

6500 SECURITY GATEWAY



Check Point's 6500 Next Generation Firewall offers a fully integrated, unified solution tuned to deliver maximum security against 5th generation threats without compromising performance. 6500 Security Gateways provide the most advanced threat prevention security for demanding enterprise networks.




Gen V Dexterity

AI Driven
Threat Prevention



Augmented SSL Inspection

Powerful Gateways to Manage
Encrypted Traffic Inspection



Bonded with Infinity Architecture

More than just
Network Security

PERFORMANCE HIGHLIGHTS

Gen II Security: Firewall	Gen III Security: NGFW ¹	Gen V Security: Threat Prevention + SandBlast ²
20.6 Gbps	6.8 Gbps	3.4 Gbps

Performance measured with an enterprise testing conditions. Additional performance details on page 4. 1: Includes Firewall, Application Control, and IPS. 2: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection.

WELCOME TO THE FUTURE OF CYBER SECURITY

6500

Enterprise-grade security, performance and reliability

The Check Point 6500 Next Generation Security Gateway combines the most comprehensive security protections to safeguard your mid-size enterprise.

The 6500 Turbo model is a 1U Next Generation Security Gateway with one I/O expansion slot for higher port capacity, redundant fans, redundant AC or DC power supply options, a 240 GB SSD disk, and optional Lights-Out Management (LOM) for remote management. This powerful Next Generation Security Gateway is optimized to deliver the most advanced threat prevention to secure your critical assets and environments.

Key Features & Benefits

- Advanced Threat Prevention 1st time prevention of known and zero-day threats
- Uncompromising Performance Achieve up to 3.4 Gbps of threat prevention throughput
- Secure Encrypted Traffic Consolidate SSL inspection into one integrated security platform



THE CYBER SECURITY ARCHITECTURE OF THE FUTURE

Enterprise Security Gateways

ONE SECURITY PLATFORM

Leveraging unified threat intelligence and open interfaces

REAL-TIME THREAT PREVENTION

Blocking the most sophisticated attacks before they infiltrate the network


CONSOLIDATED MANAGEMENT

Single management, modular policy management and integrated threat visibility

WELCOME TO THE FUTURE OF CYBER SECURITY

6500 SECURITY GATEWAY

- 1 Sync 10/100/1000Base-T RJ45 port
- 2 RJ45/micro USB console port
- 3 One network card expansion slot
- 4 8x 10/100/1000Base-T RJ45 ports
- 5 Management 10/100/1000Base-T RJ45 port
- 6 2x USB ports for ISO installation
- 7 Lights-Out Management port



SPOTLIGHT

Prevent Known and Zero-day Threats

Zero-day protection offering network security with evasion-resistant malware detection and complete protection from the most advanced attacks, ensuring quick delivery of safe content to users.




Complete Security: Simple Offering

Flexible cost-effective bundles. Subscription and support offered together for NGFW, NGTP or NGTX (sandboxing) in either direct or collaborative premium support for 1, 3 or 5 years.

Flexible I/O Options

The 6500 Turbo configuration includes 10 on-board 1 GbE copper ports. Add additional I/O as you like in the one expansion slot; 8x 1GbE copper, 4x 1GbE fiber, 4x 10GbE SFP+ or one of two Bypass (Fail-open) options.



Remote Management and Monitoring

A Lights-Out Management (LOM) card provides out-of-band remote management to remotely diagnose, start, restart and manage the appliance from a remote location. Also use LOM for remote installs of the GAIa OS.

ENTERPRISE-GRADE PLATFORM

		1 GbE (copper)	1 GbE (fiber)	10 GbE	Memory	Redundant Power	LOM
6500	Turbo	10	0	0	16 GB	●	●
	Maximums	18	4	4	32 GB	●	●

WELCOME TO THE FUTURE OF CYBER SECURITY

Performance

Enterprise Testing Conditions

- 3.4 Gbps of Threat Prevention¹
- 6.8 Gbps of NGFW²
- 7.8 Gbps IPS
- 20.6 Gbps of firewall throughput

Ideal Testing Conditions

- 22.8 Gbps of UDP 1518 byte packet firewall throughput
- 4.3 Gbps of AES-128 VPN throughput
- 140,000 connections per second, 64 byte response
- 4/8M concurrent connections, 64 byte response³

1: Includes Firewall, Application Control, URL Filtering, IPS, Antivirus, Anti-Bot and SandBlast Zero-Day Protection. 2: Includes Firewall, Application Control and IPS. 3: Performance measured with default/maximum memory.

Additional Features

Highlights

- 1x CPU, 4x physical cores (total), 8x virtual cores (total)
- 1x 240 GB SSD storage
- 2 redundant AC power supplies, DC PSU option
- 16 GB memory, 32 GB option
- Lights-Out Management card
- Virtual Systems (default/max mem): 20/20

Network Expansion Slot Options (1 of 1 slots open)

- 8x 10/100/1000Base-T RJ45 port card, up to 18 ports
- 4x 1000Base-F SFP port card, up to 4 ports
- 4x 10GBase-F SFP+ port card, up to 4 ports

Content Security

First Time Prevention Capabilities

- CPU-level, OS-level and static file analysis
- File disarm and reconstruction via Threat Extraction
- Average emulation time for unknown files that require full sandbox evaluation is under 100 seconds
- Maximal file size for Emulation is 100 MB
- Emulation OS Support: Windows XP, 7, 8.1, 10

Applications

- Use 8,000+ pre-defined or customize your own applications
- Accept, prevent, schedule, and apply traffic-shaping

Data Loss Prevention

- Classify 700+ pre-defined data types
- End user and data owner incident handling

Content Security (continued)

Dynamic User-based Policy

- Integrates with Microsoft AD, LDAP, RADIUS, Cisco pxGrid, Terminal Servers and with 3rd parties via a Web API
- Enforce consistent policy for local and remote users on Windows, macOS, Linux, Android and Apple iOS platforms

Network

Network Connectivity

- Total physical and virtual (VLAN) interfaces per appliance: 1024/4096 (single gateway/with virtual systems)
- 802.3ad passive and active link aggregation
- Layer 2 (transparent) and Layer 3 (routing) mode

High Availability

- Active/Active L2, Active/Passive L2 and L3
- Session failover for routing change, device and link failure
- ClusterXL or VRRP

IPv6

- NAT66, NAT64, NAT46
- CoreXL, SecureXL, VRRPv3

Unicast and Multicast Routing (see sk98226)

- OSPFv2 and v3, BGP, RIP
- Static routes, Multicast routes
- Policy-based routing
- PIM-SM, PIM-SSM, PIM-DM, IGMP v2 and v3

Physical

Power Requirements

- Single Power Supply rating: 275W
- AC power input: 100 to 240V (47-63Hz)
- Power consumption max: 88.4W
- Maximum thermal output: 301.65 BTU/hr.

Dimensions

- Enclosure: 1RU
- Dimensions (WxDxH): 17.24 x 20 x 1.73 in. (437.9 x 508 x 44mm)
- Weight: 17.53 lbs. (7.95 kg)

Environmental Conditions

- Operating: 0° to 40°C, humidity 5% to 95%
- Storage: -20° to 70°C, humidity 5% to 95% at 60°C

Certifications

- Safety: UL, CB, CE, TUV GS
- Emissions: FCC, IC, CE, VCCI, RCM/C-Tick
- Environmental: RoHS, WEEE, REACH¹, ISO14001¹

¹. factory certificate

WELCOME TO THE FUTURE OF CYBER SECURITY

ORDERING 6500 SECURITY GATEWAYS

SECURITY APPLIANCE ¹	SKU
6500 Turbo configuration: includes 10x 1GbE copper ports, 16 GB RAM, 240GB SSD, 2x AC PSUs, Lights-Out Management (LOM).	CPAP-SG6500-TURBO

¹ 1, 3 and 5 year NGFW, NGTP and SandBlast (NGTX) packages with Direct Premium support are available in the online product catalog.

Accessories

INTERFACE CARDS AND TRANSCEIVERS	
8 Port 10/100/1000 Base-T RJ45 interface card	CPAC-8-1C-C
4 Port 1000Base-F SFP interface card; requires additional 1000Base SFP transceivers	CPAC-4-1F-C
SFP transceiver module for 1G fiber ports - long range (1000Base-LX)	CPAC-TR-1LX-C
SFP transceiver module for 1G fiber ports - short range (1000Base-SX)	CPAC-TR-1SX-C
SFP transceiver to 1000 Base-T RJ45 (Copper)	CPAC-TR-1T-C
4 Port 10GBase-F SFP+ interface card	CPAC-4-10F-6500/6800-C
SFP+ transceiver module for 10G fiber ports - long range (10GBase-LR)	CPAC-TR-10LR-C
SFP+ transceiver module for 10G fiber ports - short range (10GBase-SR)	CPAC-TR-10SR-C
MEMORY	SKU
Memory upgrade kit from 16GB to 32GB for 6500 Security Gateways	CPAC-RAM16GB-6500
SPARES AND MISCELLANEOUS	SKU
AC power supply for 6500 Security Gateways	CPAC-PSU-AC-6500
DC power supply for 6500 Security Gateways	CPAC-PSU-DC-6500
Lights-Out Management module	CPAC-LOM-6500/6800-C
Slide rails for 6000 Security Gateways (22" - 32")	CPAC-RAILS-6000
Extended slide rails for 6000 Security Gateways (24" - 36")	CPAC-RAILS-EXT-6000

6500 SECURITY GATEWAY

- 1 Redundant AC or DC power supplies
- 2 Cooling fans

