

OceanStor 6810/18510/18810 New-Gen High-End Hybrid Flash Storage Systems

Huawei's New-Gen OceanStor 6810/18510/18810 High-End Hybrid Flash Storage Systems are designed to provide excellent data services for critical enterprise applications. The systems feature the industry-leading SmartMatrix architecture, active-active solution for SAN and NAS, flash acceleration technology, high-performance hardware platform, and various solutions designed to improve efficiency and data protection. Together, they provide optimal reliability and performance to meet the data storage requirements of various scenarios, including email systems of large enterprises, large-scale data warehouses, massive small-files sharing, and cloud computing. This makes them an ideal choice for the government, telecom, finance, manufacturing, and healthcare sectors.

7-Nines Reliability

Sustainable development is becoming a key concern of enterprises in various sectors, prompting many to upgrade to intelligent storage systems. Moreover, diverse services and data types are raising the requirements for IT systems. Now, they must be able to consolidate multiple types of services and ensure stable service running. Huawei OceanStor 6810/18510/18810 high-end hybrid flash storage systems meet these needs from five dimensions: architecture, product, data, solution, and O&M. Their reliable end-to-end architecture ensures 99.99999% service availability for all service scenarios.

Architecture – fully interconnected design

Huawei OceanStor 6810/18510/18810 storage adopts the innovative SmartMatrix architecture that comprises the front-end and back-end full-mesh and multi-controller multi-active deployment, achieving high reliability and performance balancing.

Specifically, this architecture tolerates the failure of three out of four or seven out of eight controllers without interrupting services, setting a new benchmark for storage reliability. Each front-end interface module is connected to four controllers, which allows services on the faulty controller to fail over to the normal controller within seconds, without disrupting any host links or affecting upper-layer services. The fully symmetric active-active design (meaning the LUNs do not belong to any controller) enables the application server to access LUNs through any controller. As for performance balancing, thanks to the load balancing algorithm, services simultaneously run on multiple controllers to reduce the pressure on each one controller. In the unlikely event that any controller fails, other controllers can take over services smoothly without interrupting any services.

Product – enhanced hardware and software

Huawei OceanStor 6810/18510/18810 storage uses a fully redundant architecture and supports dual-port NVMe disks and hot swap to prevent single points of failure.

Specifically, the hot-swappable I/O interface module makes replacing and upgrading interface modules easier. What's more, with the Huawei RAID 2.0+ technology, it takes only 15 minutes to reconstruct a 1 TB disk, greatly improving data reliability. The RAID reconstruction technology allows you to promptly adjust the RAID member disks in the event of a disk failure, and the service will not be interrupted even if more than 3 disks fail consecutively.

Data- ransomware protection solution

Huawei OceanStor 6810/18510/18810 storage adopts the ransomware protection solution that features the Air Gap technology and high-density snapshots to effectively defend against ransomware attacks and support fine-grained data restoration, protecting your systems from ransomware loss. What's more, the end-to-end data encryption solution, comprising the HyperEncryption function and the native or external key management deployments, works with the storage system to implement static data encryption, preventing data leakage even in the event of hard disk loss.*

Solution – gateway-free active-active solution

Huawei OceanStor 6810/18510/18810 storage runs core enterprise services, meaning it tolerates no data loss or service interruption. The active-active solution is an ideal choice for such scenarios. Huawei OceanStor 6810/18510/18810 storage uses the gateway-free active-active solution for SAN and NAS to reduce faulty nodes, simplify system deployment, and improve system reliability. In addition, the active-active solution implements load balancing active-active mirroring and non-disruptive cross-site failover, preventing core applications from breaking down. What's more, the active-active solution can be smoothly upgraded to a geo-redundant 3DC data protection solution to provide a higher level of data protection.

O&M- non-disruptive upgrade

Huawei OceanStor 6810/18510/18810 storage adopts the modular software architecture, meaning 95% of upgrades can be performed in the user mode within 1 second, with no need to restart controllers. In the remaining scenarios that require controllers to be restarted, the unique front-end interconnect I/O module connects four internal links to each controller in an enclosure, which means that during the upgrade, if any controller restarts, service links will seamlessly fail over to another controller without affecting the host or links.

Flash-Like Performance

Dynamic adaptive data layout (DADL)

Huawei OceanStor 6810/18510/18810 storage adopts the global cold and hot data sensing and data collaboration algorithms that support system auto-learning in all scenarios. The algorithms enable the storage systems to sense changes in service models, and hot and cold data, thus helping promptly locate hot data in various scenarios. What's more, the elastic convergence of storage cache and tiers resolves the challenges faced in the traditional practice and fuels data acceleration, which results in optimal data layout and simplified configuration.

Lossless ROW architecture

The systems adopt redirect-on-write (ROW) and multi-point-in-time technologies to build lossless snapshots and clones. Snapshots can be created by creating pointers, with no need to copy data, and the overall storage performance will not be affected if snapshots are activated on mass. What's more, the storage performance remains at a high level even when the data protection feature is enabled.

Leading specifications

The storage systems use a multi-core and multi-thread high-performance processing platform. Specifically, controllers are interconnected using the remote direct memory access (RDMA) technology, enabling a single enclosure to provide up to 1280 Gb system bandwidth. In addition, the storage systems support end-to-end NVMe architecture. The front-end of the system is equipped with 768 host ports, which supports 32Gbps FC-NVMe/25Gbps RoCE; the back-end adopts the NVMe over Fabrics (100 Gbps) and SAS 3.0 (12 Gbps) high-speed ports, which meets users' requirements to access core databases at high concurrency and low latency.

Endless Evolution

- Huawei OceanStor 6810/18510/18810 storage supports hybrid workloads such as blocks, files, virtualization, and containers, which meets the users' elastic service development requirements, improves storage resource utilization, and effectively reduces the total cost of ownership (TCO). In addition, balanced SAN and NAS services, supercharged by the Hyper and Smart features, provide diversified data protection and efficiency improvement capabilities for block and file systems. This provides users with comprehensive services.
- The combination of private and public clouds, cloud backup, and container services have supercharged the user's smooth migration of data to the cloud.
- DME interconnects with Ansible and mainstream IT Service Management platforms like ServiceNow, reducing O&M costs.

Technical Specifications

Model	OceanStor 6810	OceanStor 18510	OceanStor 18810
Hardware Specifications			
Maximum number of controllers	16	32	32
Maximum cache (dual controllers, grows with the expansion of controllers)	512 GB to 16 TB	512 GB to 32 TB	1 TB to 32 TB
Supported storage protocols	FC, iSCSI, NFS, CIFS, FC-NVMe, NVMe over RoCE, FTP*, HTTP*, NDMP, S3*		
Front-end channel port types	8/16/32 Gbps FC/FC-NVMe, 1/10/25/40/100 Gbps Ethernet, 25 Gbps NVMe over RoCE		
Back-end channel port types	100 Gbps RDMA/SAS 3.0		
Maximum number of hot-swappable I/O modules per controller enclosure	28		
Maximum number of front-end host ports per controller enclosure	80	96	
Maximum number of disks	3200	6400	9600
Hard disk types	NVMe TLC SSD, SAS TLC SSD, SAS, NL-SAS		
Supported SCMs	800 GB/1.6 TB*		
Software Specifications			
Supported RAID levels	RAID 5, 6 and RAID-TP (tolerating simultaneous failure of three disks)		
Value-added software	SmartAcceleration, SmartVirtualization, SmartMigration, SmartThin, SmartQoS, SmartQuota, SmartMulti-tenant, SmartCompression, SmartDedupe, SmartContainer*, HyperSnap, HyperReplication, HyperClone, HyperMetro, HyperCDP, HyperLock, HyperMetro-Inner, HyperDetect, HyperEncryption, CloudBackup*		
Storage management software	DeviceManager, UltraPath, eService		
Electrical Specifications			
Power supply	200 V to 240 V AC \pm 10%, 240 V DC \pm 20%	Cabinet: 200 V to 240 V AC \pm 10%, 346 V to 415 V AC \pm 10%, 192 V to 288 V DC	
Dimensions (H x W x D)	Controller enclosure: 175 mm x 447 mm x 865 mm SAS disk enclosure: 86.1 mm x 447 mm x 410 mm NVMe disk enclosure: 86.1 mm x 447 mm x 620 mm NL-SAS disk enclosure: 175 mm x 447 mm x 488 mm	Maximum cabinet dimensions: 1200 mm x 600 mm x 2000 mm Controller enclosure: 175 mm x 447 mm x 865 mm SAS disk enclosure: 86.1 mm x 447 mm x 410 mm NVMe disk enclosure: 86.1 mm x 447 mm x 620 mm NL-SAS disk enclosure: 175 mm x 447 mm x 488 mm	
Weight(including disk units)	Controller enclosure \leq 88.2 kg SAS disk enclosure \leq 19.65 kg NL-SAS disk enclosure \leq 43.9 kg Smart NVMe disk enclosure \leq 33.95 kg	Controller enclosure \leq 88.2 kg SAS disk enclosure \leq 19.65 kg NL-SAS disk enclosure \leq 43.9 kg Smart NVMe disk enclosure \leq 33.95 kg System cabinet \leq 700 kg Disk cabinet \leq 600 kg	
Operating temperature	-60 m to +1800 m altitude: 5°C to 35°C (cabinet) or 40°C (enclosure) 1800 m to 3000 m altitude: The maximum temperature threshold decreases by 1°C for every altitude increase of 220 m		
Operating humidity	10% to 90% R.H.		

*Contact Huawei sales staff if you need this specification.

For More Information


To learn more about Huawei storage, please contact your local Huawei office or visit the Huawei Enterprise website: <http://e.huawei.com/en/>.



Huawei Enterprise Business App



Huawei IT Products & Solutions - LinkedIn



Huawei IT Products & Solutions - YouTube



Copyright © Huawei Technologies Co., Ltd. 2022. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without the prior written consent of Huawei Technologies Co., Ltd.

Huawei Technologies Co., Ltd

Bantian Longgang District
Shenzhen 518129, P.R. China
Tel: +86-755-28780808

Trademarks and Permissions

HUAWEI, HUAWEI, and are trademarks or registered trademarks of Huawei Technologies Co., Ltd.

Other trademarks, product, service and company names mentioned are the property of their respective holders.

www.huawei.com

Disclaimer

The content of this manual is provided "as is". Except as required by applicable laws, no warranties of any kind, either express or implied, including but not limited to, the implied warranties of merchantability and fitness for a particular purpose, are made in relation to the accuracy, reliability or contents of this manual.

To the maximum extent permitted by applicable law, in no case shall Huawei Technologies Co., Ltd be liable for any special, incidental, indirect, or consequential damages, or lost profits, business, revenue, data, goodwill or anticipated savings arising out of, or in connection with, the use of this manual.